



MRD-160

Order No.: 0104370

Price upon request

PRODUCTINFOS

PA mid-high range driver, 60 W, 8 Ω

- 25 mm (1") top-class professional driver
- Reproduction of high efficiency and very linear frequency response
- Very compact size, high power capability
- For PA speaker systems of high requirements, perfectly suitable for combination with 30 cm and 25 cm (12" and 10") bass speakers
- Replacement voice coil SP-30PAX/VC is available at option
- Suitable for horns MRH-200 and MRH-180

TECHNICAL SPECIFICATIONS

MRD-160

| | |
|-------------------------|--------------|
| Impedance (Z) | 8 Ω |
| Frequency range | fx-18,000 Hz |
| Resonant frequency (fs) | 750 Hz |

MRD-160

| | |
|---|------------------|
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | 2,000 Hz |
| Power rating (RMS) | 60 W |
| Peak music power output (MAX) | 150 W |
| Sensitivity | 109 dB/W/m |
| Voice coil diameter | Ø 44.4 mm |
| Magnet diameter | Ø 110 mm |
| Mounting cutout | dep. on horn |
| Mounting depth | dep. on horn |
| Dimensions | Ø 115 mm x 53 mm |
| Outside diameter | Ø 115 mm |
| Width | Ø 115 mm |
| Depth | 53 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 1.7 kg |
| Packing unit | 1 |